RCLDR-FS1000-42U-A

LDR Assembled 42U Server Rack Cabinet 600x1000mm

It has toughened glass front door with solid metal door panel, Back solid metal door with spring handle locks

- ◆ Front toughened smoky glass door
- ◆ Back solid metal door with spring handle lock
- ◆ Removable solid metal side panels with bolt locks
- ◆ Enhanced 130 degrees operation angle hinge
- ◆ Top & Bottom wire path, hole size can be customised
- ◆ Top can be fixed with 2~4 fans for cooling.
- ♦ With heavy-duty swiveling wheels& adjustable feet
- ◆ RU marked 2.0 mm mounting rails, thickness for body

1.2mm

- ◆ Disassemble package
- ◆ Easily to assemble by air tool
- ◆ Max Static Bearing capacity: 800 KG
- ◆ Protection: IP20
- Complies with ANSI/EIA RS-310-D, IEC297-2, DIN41491; PART1, DIN41494; PART7, ETSI
- Surface Finish: Degrease, acid pickling, rust prevention and Parkerizing, pure water cleaning, static electricity powder coating
- Color: Black RAL9005

Application

- · Telecommunication equipment
- · CCTV
- · Security and broadcasting
- · Active equipment
- · DATA CENTER






RCLDR-FS1000-42U-A SAMPLE gallery: 600*1000 mm 42U



Front glass door with lock



Back solid metal door



Top fan trays for ventilation



Marked 19" Rails + accessories



| NO. | Item | 600 wide | Materials | Treatment | Note |
|-----|-----------------|----------|---------------------|----------------|----------------|
| 1 | Frame | 2 | 1.2mm SPCC steel | Powder coating | |
| 2 | Front Door | 1 | Glass 5mm thickness | ١ | metal border |
| 3 | Side Door | 2 | 1.2mm SPCC steel | Powder coating | Removable |
| 4 | Back Door | 1 | 1.2mm SPCC steel | Powder coating | |
| 5 | Lock | 2 | \ | ١ | Handle Lock |
| 6 | Top cover | 1 | 1.2mm SPCC steel | Powder coating | |
| 7 | Rear door panel | 1 | 1.2mm SPCC steel | Powder coating | |
| 8 | Fan unit | 1 | 1.2mm SPCC steel | Powder coating | |
| 9 | Ac fan | 4 | \ | ١ | D>800,4 pcs |
| 10 | Bottom panel | 1 | SPCC T=1.2 | Powder coating | Optional parts |
| 11 | Earthing cable | 1 | Y/G cable | \ | 25 cm |
| 12 | Castors tray | 4 | SPCC T=2.0 | Powder coating | |
| 13 | Castors | 4 | \ | \ | |
| 14 | Ajustable feet | 4 | Steel | Brass plated | M12 |
| 15 | Mounting angle | 6 | SPCC T=1.2 | Powder coating | |
| 16 | 19inch rails | 4 | SPCC T=2.0 | Powder coating | |
| 17 | Vertical C/M | \ | SPCC T=1.2 | Powder coating | Only for 800 W |

DISASSEMBLE PACKAG

| Part Number Example | | Description | | | | | | | | | |
|---------------------|-----|---|----|-----------|------------|--------------|------------|-------|--|--|--|
| RCLDR-FS1000-42UA | | LDR Assembled 42U Server Rack Cabinet (600mm x 1000mm) Glass Door, 1x 8-Port PDU, 1x 4-Way Fan, 2x Fixed Shelves - Black Metal Construction | | | | | | | | | |
| | | WB | NC | 6 | 0 | 42 | 15 | В | | | |
| | LDR | | | 600mm (W) | 1000mm (D) | 42U Capacity | Door Style | Black | | | |

Note: Hardware: 4 fans,2 fixed shelves,4x casors,4x fixed feet,20 sets cage nuts

