



COMMERCIAL DISPLAY CN6501-1C

Key Features

- Offers 24/7 non-stop playback in both landscape and portrait modes.
- Single USB-C port provides a one-cable solution for diverse content sharing.
- Intuitive signage player supports various content formats, scheduling, and uninterrupted playback.
- Effortless wireless casting with AirPlay, Miracast, and Chromecast for seamless connectivity
- High brightness of 520 nits delivers vibrant colors and enhanced image clarity



Product Description

Transform your visual communication with the CN Series, boasting 4K Ultra HD clarity and flexible display orientations for both landscape and portrait modes. Perfect for corporate and educational settings, this series ensures high performance and sustainable operation. It features an easy-to-use signage player for diverse content management and continuous playback. Effortlessly connect with wireless casting options like AirPlay, Miracast, and Chromecast. Available in sizes from 43" to 75" with HDMI input, the CN Series caters to all your communication needs, enhancing every presentation and connection.

Visit Us

www.viewsonic.com

DISPLAY

Panel Size:	65"
Type/ Tech:	TFT LCD Module., DLED backlight
Display Area (mm):	1428.48 (H)x803.52(V) (64.5")
Native Resolution:	3840 x 2160
Aspect Ratio:	16:9
Colors:	1.07G (8bits + FRC)
Brightness:	520 nits (typ.)
Contrast Ratio:	5000:1
Response Time:	6.5ms
Viewing Angles:	H = 178, V = 178 typ.
Backlight Life:	50,000 hours
Surface Treatment:	Anti-Glaire, 3H hardness, Haze 25%
Orientation:	Landscape & Portrait

PLATFORM

Processor:	Quad-core
RAM:	4GB
Storage:	32GB

INPUT

HDMI:	2.1 x2 (HDCP 2.2)
RS-232:	x 1
IR Pass Thru:	x 1

OUTPUT

RS232:	x 1
IR Pass Thru:	x1

LAN

RJ45:	x 1
-------	-----

USB

Type A:	2.0 x 2
Type C:	x1 ((DP1.2, PD 65W, USB2.0)

SPEAKERS

10Wx2

EMBEDDED OS

Android 14

POWER

Voltage:	100-240V AC +/- 10%
Consumption:	On:180W ; Off<0.5W

ERGONOMICS

Wall Mount (VESA®):	500 x 500
----------------------	-----------

OPERATING CONDITIONS

Temperature (° C):	0 to 40°C
Humidity:	20%-80% RH

OPERATING HOURS

7/24

DIMENSIONS (W X H X D)

Physical (inch / mm):	57.39 x 32.77 x 2.71 in. / 1457.7 x 832.4 x 68.8 mm
Packaging (inch / mm):	64.57 x 38.98 x 6.46 in / 1640 x 990 x 164 mm

WEIGHT

Net (lb / kg):	39.02lb / 17.7kg
Gross (lb / kg):	60.4 lb / 27.4 kg

REGULATIONS

BIS, WPC

PACKAGE CONTENTS

Remote Control with batteries 2. Quick Start Guide 3. Power Cables 4. Wall Mount & Screw x 4 5. RS232 adapter 6. Compliance statement
--