



Key Features

- Windows 11 Pro
- Ideal Integrated Solution for ViewBoard® Interactive Displays and Presentation Display
- Powerful Intel® 12th Core Processors embeded TPM2.0
- Improved System Stability, Security, & Thermal Control



Product Description

Seize the power to get more done when you sync your ViewBoard® interactive displays and Presentation Displays with the ViewSonic VPC35-W53-G1 slot-in PC. Integrated with exceptional performance from Intel® processors, 16GB DDR4 memory, and 256GB SSD storage, the experience enhances computing performance to breeze through complex classes and collaborations. Plug into pure productivity with dual-band WiFi, Bluetooth 5.1, and a range of ports, including 4K HDMI, DP1.4, USB 3.0, and Gigabit LAN RJ45 for faster workflows.

Visit Uswww.viewsonic.com

SOFTWARE

Operating System:	Windows 11 Pro
-------------------	----------------

CORE

CPU:	Intel® Core™ i5-1240P 1.7G Turbo boost 4.4G
------	---

Graphics:	Integrated Intel® iris Xe Graphics (80EU) Total Available Graphics Memory: 32GB Max Resolution up to 7680x4320@60Hz (DP)
-----------	--

MEMORY

Type:	DDR4 SO-DIMM
-------	--------------

Capacity:	16GB (Up to 32GB)
-----------	-------------------

STORAGE

Dimension:	M.2 2280 (22 x 80 mm)
------------	-----------------------

Capacity:	256GB SSD
-----------	-----------

Interface:	PCIE and SATA 3
------------	-----------------

INPUT

MIC(Microphone):	x1
------------------	----

OUTPUT

DisplayPort:	x1 (1.4 max. resolution 7860x4320@60Hz)
--------------	---

HDMI:	x 1 (2.0 max, resolution 3840x2160@60Hz)
-------	--

Audio:	x 1 Line out
--------	--------------

LAN

RJ45:	x1
-------	----

WIRELESS / BLUETOOTH

Wireless / Bluetooth:	Intel® Wi-Fi 6 AX200 802.11 a/b/g/n/ac/ax 2T2R + BT5.1
-----------------------	--

USB

Type A:	USB 3.0 x 4
---------	-------------

Type C:	x 1 (data only)
---------	-----------------

BUNDLE SOFTWARE

Bundle Software:	myViewBoard for Window Adobe Reader BIOS Winflash tool FinchGuard (Watch Dog)
------------------	--

POWER

Voltage:	DC 12-19V/ 8A
----------	---------------

Consumption:	96 W (Max)
--------------	------------

OPERATING CONDITIONS

Temperature (° C):	-5~40°C
--------------------	---------

Humidity:	10% ~ 90% @ 40°C Non-condensing.
-----------	----------------------------------

DIMENSIONS (W X H X D)

Physical (inch / mm):	7.95 x 4.83 x 1.18 in / 202 x 122.6 x 30 mm
-----------------------	---

Packaging (inch / mm):	10.51 x 7.56 x 2.83 in / 267x 192 x 72mm
------------------------	--

WEIGHT

Net (lb / kg):	1.33lb/0.6kg
----------------	--------------

Gross (lb / kg):	2.14 lb/0.97kg
------------------	----------------

REGULATIONS

REGULATIONS:	cTUVus, FCC/ICES003, FCC ID/ ICID, TPCH DoC, Packing waste, CA65 DoC, CE EMC, (LVD or CB,CE R&TTE, ErP, RoHS Green BOM & DoC,REACH SVHC,WEEE
--------------	--

PACKAGE CONTENTS

PACKAGE CONTENTS:	1. VPC OPS 2. Quick Start Guide
-------------------	------------------------------------